1100 Series 1106D-E70TAG5 Diesel Engine - Electropak

228 kWm standby power @ 1800 rpm

Building upon Perkins proven reputation within the power generation industry, the 1100 Series range of ElectropaK engines now fit even closer to customers needs.

In the world of power generation success is only gained by providing more for less. With the 1106D-E70TAG5 Perkins has engineered even higher levels of reliability, yet lowered the cost of ownership.

1100A units are designed for territories that do not require compliance to EPA or EU emissions legislation. These engines are assembled around optimal, efficient manufactuing processes with state-of-the-art technology. They are built to provide the exact power solution for customers who sell their applications into lesser regulated countries.

Focusing on our common platform theme, changes to engine envelope dimensions and connection points have been kept to a minimum.



- The Perkins® 1106D-E70TAG5 delivers up to 250 kVA standby at 50 Hz and 200 kWe at 60 Hz, providing greater productivity through an improved power to weight ratio
- This world-class power density has been achieved in a 7 litre engine, using an electronic fuel injection system; making this engine robust for all markets, with the ability to cope with the variation of fuel qualities around the world
 - The 1106D has been designed for excellent load acceptance to ensure your facility is powered quickly at all conditions

Low operating costs

- Service intervals are set at 500 hours as standard assuming approved fuels and lubrication oils are used
- Perkins provides comprehensive warranty cover for two years (up to 3,000 hours), with three years on major engine components
- A low usage warranty package is also available



World class product support

- Through an experienced global network of distributors and dealers, fully trained engine experts deliver total service support around the clock, 365 days a year. They have a comprehensive suite of web based tools at their finger tips, covering technical information, parts identification and ordering systems, all dedicated to maximising the productivity of your engine
- Perkins actively pursues product support excellence by insisting our distribution network invest in their territory to provide you with a consistent quality of support across the globe
- Throughout the entire life of a Perkins engine, we provide access to genuine OE specification parts giving 100% reassurance that you receive the very best in terms of quality for lowest possible cost... wherever your Perkins powered machine is operating in the world

Discover more

www.perkins.com/esc

www.perkins.com/distributor
To find your local distributor


Engine Speed rpm	Type of Operation	Typical Generator Output (Net)		Engine Power			
				Gross		Net	
		kVA	kWe	kWm	bhp	kWm	bhp
1800	Standby (maximum)	250	200	228	306	218	292




1100 Series 1106D-E70TAG5 Diesel Engine - ElectropaK

228 kWm standby power @ 1800 rpm







Engine specification

- Tropical radiator pipes and guards
- Flywheel housing
- Flywheel and starter ring
- Oil filters
- Starter motor
- Air cleaners and brackets
- Lubricating oil sump
- Alternator
- Induction manifolds
- Exhaust manifolds
- Fuel filter
- Cold start aid
- Engine mountings

Fuel Consumption						
Engine Cheed	1800 rpm					
Engine Speed	kW	g/kWh	l/hr			
110% of Prime Power	234.5	210.2	59.1			
Prime Power	211.1	214.9	54.4			
75% of Prime Power	158.3	229.1	43.5			
50% of Prime Power	105.6	233.4	29.5			
25% of Prime Power	52.8	253.0	16.0			

Engine data

Number of cylinders	Vertical in-line 6 cylinder			
Bore and stroke	105 x 135 mm (4.13 x 5.31 in)			
Displacement				
Aspiration	Turbocharged aftercooled			
Cycle	4 stroke			
Combustion system	Direct injection			
Compression ratio	16.8:1			
Engine rotationAnti-clockwise viewed on flywheel				
Cooling system	Liquid			
Total lubrication capacity	16.5 litres (4.36 US gal)			
Total coolant capacity	21 litres (5.5 US gal)			
Dimensions - Length with air of	cleaner1763 mm (69.4 in)			
Width	768 mm (30.2 in)			
Height	1142 mm (45 in)			
Dry weight				

Final weight and dimensions will depend on completed specification

Photographs are for illustrative purposes only and may not reflect final specification.

All information in this document is substantially correct at time of printing and may be altered subsequently. Publication No. PN3074/08/14 Produced in England ©2014 Perkins Engines Company Limited **Perkins Engines Company Limited**

Peterborough PE1 5FQ United Kingdom Telephone +44 (0)1733 583000 Fax +44 (0)1733 582240

www.perkins.com

